







*Max. zulässige Druckstufen (PB) entnehmen Sie bitte den Angaben der Schneidringverschraubungen.

*Max. allowed pressure (PB) see at the data from the compression couplings.

Anschlussart Connection	DN	LW	D	RA	Ca. Maße Approx. Dimensions			
					L	L10	i	SW
01 • Rohrgewinde • DIN ISO 228 • <i>BSP Female Thread</i> • <i>DIN ISO 228</i> 	4	5,0	G 1/8"		69	26,0	9	22
	6	6,0	G 1/4"		69	26,0	12	22
	10	9,0	G 3/8"		73	28,0	12	27
	13	11,5	G 1/2"		85	32,0	14	30
	20	18,0	G 3/4"		96	40,5	17	41
	25	22,0	G 1"		113	51,0	19	46
	32	30,0	G 1 1/4"		110	62,0	20	60
	40	35,0	G 1 1/2"		120	65,0	24	70
	50	44,0	G 2"		140	72,0	28	85
	02 • NPT-Innengewinde • ANSI B 2.1 • <i>NPT Female Thread</i> • <i>ANSI B 2.1</i> 	4	5,0	1/8"-27 NPT		69	26,0	12
6		6,0	1/4"-18 NPT		69	26,0	17	22
10		9,0	3/8"-18 NPT		73	28,0	17	27
13		11,5	1/2"-14 NPT		92	32,0	22	30
20		18,0	3/4"-14 NPT		97	40,5	23	41
25		22,0	1"-11,5 NPT		113	51,0	27	46
32		30,0	1 1/4"-11,5 NPT		115	62,0	28	60
40		35,0	1 1/2"-11,5 NPT		138	65,0	28	70
50		44,0	2"-11,5 NPT		140	72,0	30	85
03* • Rohrverschraubung • Leichte Reihe DIN 2353 • <i>For Compression Fitting</i> • <i>Light Series DIN 2353</i> 		4	5,0	M 12 x 1,5	6	67	41,5	10
	6	6,0	M 14 x 1,5	8	67	41,5	10	22
	8	7,0	M 16 x 1,5	10	71	41,5	11	22
	10	9,0	M 18 x 1,5	12	75	44,5	11	27
	13	11,5	M 22 x 1,5	15	84	50,0	12	30
	13	11,5	M 26 x 1,5	18	84	50,0	12	32
	20	18,0	M 30 x 2	22	102	60,5	14	41
	25	22,0	M 36 x 2	28	108	72,0	14	46
	32	30,0	M 45 x 2	35	128	86,0	16	60
	40	35,0	M 52 x 2	42	133	89,0	16	70
04* • Rohrverschraubung • Schwere Reihe DIN 2353 • <i>For Compression Fitting</i> • <i>Heavy Series DIN 2353</i> 	4	5,0	M 14 x 1,5	6				
	4	5,0	M 16 x 1,5	8	73	44,5	12	22
	6	6,0	M 18 x 1,5	10	73	44,5	12	22
	8	7,0	M 20 x 1,5	12	77	46,0	12	22
	10	9,0	M 22 x 1,5	14	84	48,5	14	27
	13	11,5	M 24 x 1,5	16	87	51,5	14	30
	13	11,5	M 30 x 2	20	91	51,5	16	32
	20	18,0	M 36 x 2	25	110	64,5	18	41
	25	22,0	M 42 x 2	30	120	78,0	20	46
	32	30,0	M 52 x 2	38	140	92,0	22	60